



ARANDA TECH INFO

Upholstered meeting table chair

This conference chair is yet another design by Pensi to be added to our collection. It is a very rich in upholstery and details, comfort is great and it gives luxury and exclusivity to any meeting room.

| | |
|---------------------------------|---|
| Designer | Jorge Pensi |
| INTRO | <ul style="list-style-type: none"> ✓ A high end exclusive upholstered meeting table chair ✓ The chairs are designed in a minimalistic way with clean lines ✓ The chair is ideal for top management offices and conference rooms ✓ The chairs can be upholstered in genuine leather, full grain leather, leather imitation, wool or fabric |
| MATERIALS & FINISHES | <ul style="list-style-type: none"> ✓ The structures are handmade in combination of solid wood and plywood ✓ Structures of inserted and glued wood composed by a) frame of 60mm thickness which forms arms, seat and backrest, b) Wooden laminates to cover each frame of each element ✓ High resistance sewing have been used ✓ Medium density foam (30 Kg/m3) for seat and backrest (F35: 25 Kg/m3). ✓ Once seat and back rest have been covered with foam a special layer of white 100 gr. fiber material is added to achieve superior comfort and softness ✓ The covers are individually sewn and upholstered for each piece: seat, backrest and arms. ✓ Total thickness: Seat 90 mm / Backrest: 110 mm / Arms: 70 mm ✓ Wood thickness: Seats (frame+laminates): 45 mm / Backrest (frame + laminates): 5-22 mm ✓ Arms, backrest and seat are united forming a unique wooden piece. The joints are made using screws and M8 bolts. ✓ Arms a made of solid wood of 30mm thickness ✓ WOOD USED: Swedish solid pine Wood and spruce from the brand "Siljan Timber AB", which is FSC certified ✓ Characteristics of foam used: ✓ Foam thickness: Seat 50 mm / backrest 50-80 mm ✓ Foam used for arms: D25 in White/Blue color, 25 kg/m3 ✓ Foams used for seat: HR 30 (high resilience), 30kg/m3 on top of slag construction which gives better seat comfort (special resistency rubber bands in squared composition) ✓ Foams used for Backrest: D25 soft, 25kg/m3 |